



DEC electronics

[www.decelectronics.com](http://www.decelectronics.com)

DISPLAY GRAFICO 128X64 FONDO AZUL CON LETRA BLANCA

MODELO: JHD-63512864E

PIN	SYMBOL	DESCRIPTION	FUNCTION
1	CS1	CHIP SELECTION	CS1=1:CHIP SELECT SIGNAL FOR IC1,High effective
2	CS2	CHIP SELECTION	CS2=1:CHIP SELECT SIGNAL FOR IC2,High effective
3	VSS	GROUND	0V (GND)
4	VDD	POWER SUPPLY FOR LOGIC CIRCUIT	+5V
5	V0	LCD CONTRAST ADJUSTMNET	
6	D/I	INSTRUCTION/DATA REGISTER SELECTION	D/I = 0 : INSTRUCTION REGISTER D/I = 1 : DATA REGISTER
7	R/W	READ/WRITE SELECTION	R/W = 0 : REGISTER WRITE R/W = 1 : REGISTER READ
8	E	ENABLE SIGNAL	
9	DB0	DATA INPUT/OUTPUT LINES	8 BIT: DB0-DB7
10	DB1		
11	DB2		
12	DB3		
13	DB4		
14	DB5		
15	DB6		
16	DB7		
17	RST	RESET SIGNAL	RSTB=0,DISPLAY OFF,DISPLAY FROM LINE 0.
18	VEE	LCD DRIVE NEGATIVE VOLTAGE	-10V
19	A	SUPPLY VOLTAGE FOR LED+	+5.0V
20	K	SUPPLY VOLTAGE FOR LED- 0V	0V